



# Refrigerated Case LED Light Fixture

5/17/11



***When quality and efficiency matter  
AEC is the clear choice!***

## Features

- High efficiency **CREE** LEDs– **21 Watts per door**
- Precision optics- **uniform light distribution**
- **Field adjustable** to accommodate variable shelf setbacks
- Low profile design – easy installation
- Maintenance free
- No hazardous materials
- Solid state power supply- one per case
- UL, NSF and Design Lights Consortium approved
- Available in 48”,54”,60”,66” and 72” lengths.
- 5 year warrantee (light fixture and power supply)

***Custom configurations on request.***



## Refrigerated Case LED Light Fixture Specifications

Nominal Length	48"	54"	60"	66"	72"
Model Number	RCLF-48	RCLF-54	RCLF-60	RCLF-66	RCLF-72
LOA	44"	50"	56"	62"	68"
Depth	1.1"	1.1"	1.1"	1.1"	1.1"
Width:					
End Fixture	1.5"	1.5"	1.5"	1.5"	1.5"
Center Fixture <sup>1</sup>	3.0"	3.0"	3.0"	3.0"	3.0"
Lumens/door	900	1,050	1,200	1,350	1,500
Watts/Door	17	19	22	25	28
CRI	83	83	83	83	83
CCT <sup>2</sup>	3,500K	3,500K	3,500K	3,500K	3,500K

<sup>1</sup> Center fixture is two "end" fixtures mounted side by side

<sup>2</sup> Other temperatures available on request

Power Supply: Meanwell Model PLN-100-36

Input: 100-240VAC. 1.4A

Output: 36VDC 2.65A

